

LIVEO-640 PWH

6.5" Waterproof 2-way Passive Wall-Mount Speaker Pair, White

Liveo series combines simplicity and elegance with sturdiness and ease of installation. Whether outdoor or indoor, low-impedance or constant-voltage line, Liveo guarantees the right solution for every application.

The housing, with minimalist and elegant lines, is made of Polypropylene with UV-resistant treatment; this ensures robustness and greater durability to exposure to sun, moisture and rain. Plastic woofer, Mylar tweeter and plastic cover of rear connections make these speakers completely waterproof. Both transducers are selected to offer not only waterproofness and high durability, but also an excellent level of audio quality.

The built-in line transformer allows the speaker to be adapted to both constant-voltage - with 3 selectable power levels - and low-impedance systems.

Each Liveo series speaker, in order to simplify installation as much as possible, comes with both a "C" bracket and a "ball-shaped" bracket, both with adjustable horizontal and vertical positions.



PRODUCT DETAILS

Key features

2-Way Passive with 40W RMS Power

IP65 Protection Rating for Outdoor/Indoor Applications

Available in Black or White Finish

UV-Resistant PP Housing

Built-in 100V Line Transformer

Power Tap Selector for 100V or low-impedance systems

Horizontal and Vertical adjustable C-Bracket and Ball-Shaped bracket

Security Wire included

Paintable Housing and Grille

Specifications

Speaker Type	2-Way Passive
IP Rating	IP65
RMS Power (@ 8ohm)	40W
Program Power (@ 8ohm)	80W
Frequency Response (-10dB)	50Hz-20kHz
Sensitivity (1w@1m)	87dB
Impedance	8ohm
Woofers	6.5" (165mm), PP cone
Tweeter	1" (25mm), Silk dome
Crossover Frequency	2.0kHz
70/100V Line Transformer with Power Tap Selector	(100V) 32W, 16W, 8W, 4W, 8Ω
Housing	UV-Resistant PP, paintable
Bracket	C-Bracket and Ball-shaped Bracket with Pan/Tilt adjustable angles and stainless-steel screws
Grille	Perforated aluminum, powder coated paint, acoustic transparent, paintable
Color	White
Product Size - no bracket included (WxDxH)	204 x 202 x 290 mm (8.0 x 7.9 x 11.4 inch)
Speaker Weight (single unit, no bracket)	2.8kg - 6.2 lbs.
Packing Size (WxDxH) (pair)	502 x 233 x 309 mm (19.8 x 9.2 x 12.2 inch)
Packing Weight (pair)	6.5kg - 14.3 lbs.